



VERTICAL FLOOR-STANDING DIGITAL SIGNAGE DISPLAY

FLR103 Super Slim Series 43", 49", 55" inch

Key Features

The displays allow consumers to seamlessly navigate a range of relevant content without interference from surrounding light or environmental conditions. The integrated, powerful operating system offers users exciting capabilities to deliver rich, engaging content with minimal operational burden required. Beyond a potential for sales and engagement, businesses also benefit from the reduced total operational costs that come with a low-maintenance, hassle-free visual display upgrade.



LED Backlight



Super Slim
Round Corner



10 Points
Capacitive Touch



Tempered Glass
on Surface



Fast Response



LAN+WIFI Network



LIFE 50000 Hours
Lifetime



Quad Core
Android Inside



7x24
Working Usage



Strong
Anti-interference



Latest Superslim Floor Standing Touchscreen Kiosk

- Infrared Technology
- Tempered Glass
- 10 point multi touch
- Screen size for 43"-65"

Ultra-thin Structure

Stylish super slim appearance with aluminum frame enclosed and built-in tempered glass. It's true thickness is only 30mm.

Full HD Stable Display

High quality 1920 x 1080 resolution ultra clear LCD Screen high brightness and superior color rendering.

Supports Android/Windows/Linux System

Support a variety of Android/Windows/Linux devices remote control, edit content synchronization. Update, expand business opportunities. However, our default and preferred OS is Android.

Supports LAN or WAN Digital Signage Content Management Software

Use Free software or simple deployment or upgrade to cloud server-based system for more complicated and advanced feature digital signage system

Diverse Customization

Diverse Customization: Single version / network version (LAN / WIFI / 3G / 4G) / touch version, camera / IR / sensing / bluetooth / interactive touch screen and other expansion capabilities, all can be customized according to customer's specific requirements such as adding corporate logo and color.

Optional Touchscreen

This IPAD Series design offers Projected Capacitive Touch (PCAP) or Touch Foil touchscreen technology for seamless design. IR technology is not applicable in this design.

SPECIFICATIONS

Technical Parameter for LCD Panel	Panel Size	43", 49, 55" real color LCD screen
	Aspect Ratio	16:9
	Max. Resolution	1920x 1080
	Dot Pitch	0.74mm(H) x 0.74mm(W)
	Number of Color	16.7M
	Brightness	450cd/m2
	Contrast Ratio	3000:1
	Touch Technology	Projective Capacitive Touch, Infrared Touch
	Responsive Time	5ms
	Panel Life	above 50000 hours
Media Player	OS	Android 7 / Windows 10
	CPU	RK3288, eight-core ARM Cortex A7 2.0 GHz Upgradeable to RK3366
	GPU	ARM Mail-764
	RAM	RAM : 4GB
	Built-in storage capacity	STORAGE : 32 GB
	WIFI	WIFI module+WIFI Antenna
Supported files	Video formats	MP4(AVI:DIVX/XVID),MPG2(DVD:VOB/MPG2), MPEG1 (VCD: DAT/MPG1)
	Audio formats	MP3
	Photo formats	JPG
	Scrolling Text	ROL(UNICODE)
	Input/output interface	USB,HDMI,VGA,RJ45
Main Hardware	Shell Material	Metal shell + Aluminum Alloy frame + toughened glass
	Surface	Metal case with powder burning; Tempered glass to protect LCD panel
	Speaker	2*10W built-in stereo speakers
	Heat Dispersion	Built-in DC fans
Power	Standby	≤3W
	Working	30W-180W
	Power supply	AC 110V - 240V, 50/60HZ
Temperature	Storage	-7 to 65 Celsius degree
	Normal Working	-5 to 65 Celsius degree
OSD Language	English, Chinese, French, German, Italian, Spanish, Arabic	



Israk Solutions Sdn. Bhd (1289622-T)

No. 20, Jalan BP 6/13, Bandar Bukit Puchong, 47120, Puchong, Selangor



<http://www.israk.my>



info@israk.my



03-8966 2405