iSRAK

ARVIA®
Innovating AV Excellence

Arvia Flip Touch

ARV TSP-32

Touch Screen Digital Signage with Stand

SIRIM Certified :

SIRIM QAS INTERNATIONAL

D&A AWARD ISLAMIC DISTINGUISHED ENTREPRENEUR AWARD 2023

THE WORLD'S BEST BRANDS FOUNDATION — THE BRANDLAUREATE

Key Features

Support Live Streaming
Support simultaneous livestreaming for Tiktok, Facebook, YouTube, twitch, Instagram, custom rtmp*

Easy Moveable
Five wheels for easy moving around.

Battery Powered
Lasts for up to 7 hours on a single charge

Convinence
support multi camera and USB web camera

Amazing Gaming Experience
Such devices allow for social gaming experiences with a strong quality

Support Most Video Conference Software
Zoom, Microsoft Team, Webex, Skype, Google Meet, GoTo Meeting and many more.

*** require additional paid software for multistream feature.*

android 12

10 points Screen Touch

Precise Touch
Milisecond fast response

Exhibition, Education & Entertainment

Can be used for teaching, learning, meeting or even for leisure lifestyle. Support Apple system and Android systemDual microphone, noise reduction more sensory

Rotate, Swivel, Tilt, Adjust

180° rotation, 130° swivel. 50° tilt and 20cm height adjustments.
Let you watch in comfort wherever you are

Install any apps from Google Playstore

Enjoy millions of Android apps, games, music, movies, TV, books, magazines & more. Anytime, anywhere, across your devices.

Specifications		
Panel	Panel Grade Panel size resolution Viewing Angle Display area Display ratio Screen brightness Backlight type Contrast Refresh frequency Pixel layout Response time Support color	New A+ LCD 32 inch 1920*1080 89/89/89/89 (Typ.)(CR≥10 940（H）×530(V) (mm) 16:09 350cd/m2（typical value） E-LED 1000:01:00 50HZ RGBVertical strip 13/5 (Typ.)(Tr/Td) 16.7M (8-bit)
Android OS	Android Version Processor RAM Storage memory WIFI Bluetooth	Android 12 MTK8788 8GB optional 128GB optional 2.4G/5G dual-band WiFi BT5.0
Touch Screen	Touch technology Touch resolution Touch points Touch medium Touch accuracy Response time Driving mode Touch interface Theoretical clicks Touch data output mode Touch calibration mode	PCAP touch screen 16384 * 9600 10 points effective touch Finger or capacitive stylus ≤2mm ≤5ms non-flooding USB More than 50 million times Coordinate output Manufacturer-specific software calibration
Camera	Pixel Field Angle Dynamic range Focusing mode	4K 8MP camera 65°±5° 96db fixed-focus
Basic functions	Battery Power supply DC MIC Speakers Language pattern Picture playback Video playback Audio playback	15000mA 19V/5A Microphone*2 6W8Ω*x2 multilingual JPG, BMP, GIF, PNG and other formats can be supported : VOB, AVI, WMV, MOV, MKV, RMVB, FLV and other formats of video and audio files Support MP3, AAC, APE, WMA, MAV and other formats of audio files
Electrical Performance	Input voltage Standby power Rated power Use environment Storage environment	AC110-220V ≤1W ≤30W Temperature -0 ° C to 60 ° C/Humidity 10%-90%RH Temperature -5 ° C to 65 ° C/Humidity 10%-90%RH
Accessories	Equipment Attachment	A set 4*16 screws *4, screwdriver *1, remote control *1, User manual*1

Israk Solutions Sdn. Bhd (1289622-T)

No 16, Wisma Arvia, Jalan IMP 1/1, Sinar Meranti Technology Park, 47120 Puchong, Selangor

http://www.israk.my info@israk.my 03-8966 2405 017-298 7182

We are ISO certified Company and Shariah Compliant